



CHAINBAR OILS

PRODUCT DESCRIPTION

Hi-Tec Chainbar Oils are made from a blend of high quality base stocks and selected additives to ensure optimum performance and long life lubrication of chains and their sprockets.

Hi-Tec Chainbar Oils contain tackifiers to resist “throw-off” ensuring that a continuous wear, reducing adhesive, lubricating film is kept on the chain mechanisms and maintaining maximum benefit of the anti-wear and anti-corrosion additives systems.

The fluidity of **Hi-Tec Chainbar Oils** ensures that they are ideally suited for manual application or for units fitted with automatic oilers. **Hi-Tec Chainbar Oils** exhibit excellent penetration of chain links.

Hi-Tec suggests that the equipment manufacturers' recommendations for grade, performance requirements and general operating conditions should be checked prior to use.

TYPICAL PROPERTIES

Property	ASTM Method	Results		
Item code (HI8-)	-	2816	2819	2820
ISO Grade	-	100	150	220
Appearance	Visual	Amber	Amber	Amber
Density Kg/Lt @ 15°C	D1298	0.894	0.897	0.901
Viscosity cSt @ 100°C	D445	11.8	15.5	20
@ 40°C	D445	100	150	220
Viscosity Index	D2270	107	106	105
Flash Point COC,°C	D92	>200	>200	>200