



BRAKE FLUID DOT 4

PRODUCT DESCRIPTION

Hi-Tec Brake Fluid Dot 4 is a premium quality brake fluid for use in hydraulic brake and clutch systems. It has a boiling point of at least 260°C and a wet boiling point of at least 160°C. Due to low deep temperature viscosity, this fluid is especially recommended for brake systems combined with SBR.

BENEFITS

- Meets IS 8654, FMVSS116 & SAE J 1703 Standards.
- It has been formulated from glycol ether. It contains glycols as lubricants, effective corrosion inhibitors and antioxidants.
- Protects both ferrous and non-ferrous metal brake system parts from corrosion.
- Gently swells rubber seals to enhance sealing & prevent system leaks.
- It has high heat stability and good low temperature performance.
- Flows smoothly in hot or cold conditions and lubricates moving parts to prolong service life.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	Typical Results
Physical form	Liquid, free from mineral oil and undissolved substances.
Colour	Clear blue
Viscosity (cSt) @ -40 °C	1500 Max
@ 100 °C	1.5 Min
ERBP (°C)	260 Min
Wet ERBP (°C)	160 Min
pH	7-11.5
Water Content (%)	<0.20
Density @ 20°C (g/mL)	1.00 – 1.10