



GEAR OIL GL-4 75W/90

PRODUCT DESCRIPTION

Hi-Tec Gear Oil GL-4 75W/90 is an API GL-4 gear lubricant is specially recommended for synchronised manual transmissions, front wheel drive transaxles gear boxes, automotive hypoid and spiral bevel axles operating at low to moderate loads.

Hi-Tec Gear Oil GL-4 75W/90 is a low viscosity product designed to minimise the problems of shift baulking at low temperatures and excessive noise when the oil is hot.

Hi-Tec Gear Oil GL-4 75W/90 is specifically designed to provide very much improved:

- Oil seal life
- Durability (gear surface life)
- Corrosion protection to yellow metals under both wet and dry conditions

Special oxidation resistant paraffinic base oils combined with high performance extreme pressure are formulated into **Hi-Tec Gear Oil GL-4 75W/90** to ensure long service life to transmission drive lines.

Gear Train Rattle and Noises Eliminated: The “stay on” properties of **Hi-Tec Gear Oil GL-4 75W/90** effectively quieten transmission drive line noise tendencies under conditions of low speed high torque, high speed low torque and shock loading.

The **Foam Inhibitors** used in **Hi-Tec Gear Oil GL-4 75W/90** avoid the natural tendency to develop foam in transmissions. Foam is undesirable because it promotes ineffective gear lubrication with resultant premature wear.

SPECIFICATIONS

Hi-Tec Gear Oil GL-4 75W/90 meets the following requirement:

API: GL-4

Hi-Tec Gear Oil GL-4 75W/90 is suitable for service fill of GMH, Ford, Daihatsu, Mazda, Mitsubishi, Nissan, Toyota and all other transmissions requiring an API GL-4 (SAE 75W/90) gear lubricant.

Always consult your vehicle owner’s manual for the manufacturer’s lubricant recommendations.

PRODUCT DESCRIPTION

Hi-Tec Gear Oil GL-4 75W/90 is an API GL-4 gear lubricant is specially recommended for synchronised manual transmissions, front wheel drive transaxles gear boxes, automotive hypoid and spiral bevel axles operating at low to moderate loads.

Hi-Tec Gear Oil GL-4 75W/90 is a low viscosity product designed to minimise the problems of shift baulking at low temperatures and excessive noise when the oil is hot.

Hi-Tec Gear Oil GL-4 75W/90 is specifically designed to provide very much improved:

- Oil seal life
- Durability (gear surface life)
- Corrosion protection to yellow metals under both wet and dry conditions

Special oxidation resistant paraffinic base oils combined with high performance extreme pressure are formulated into **Hi-Tec Gear Oil GL-4 75W/90** to ensure long service life to transmission drive lines.

Gear Train Rattle and Noises Eliminated: The “stay on” properties of **Hi-Tec Gear Oil GL-4 75W/90** effectively quieten transmission drive line noise tendencies under conditions of low speed high torque, high speed low torque and shock loading.

The **Foam Inhibitors** used in **Hi-Tec Gear Oil GL-4 75W/90** avoid the natural tendency to develop foam in transmissions. Foam is undesirable because it promotes ineffective gear lubrication with resultant premature wear.

SPECIFICATIONS

Hi-Tec Gear Oil GL-4 75W/90 meets the following requirement:

API: GL-4

Hi-Tec Gear Oil GL-4 75W/90 is suitable for service fill of GMH, Ford, Daihatsu, Mazda, Mitsubishi, Nissan, Toyota and all other transmissions requiring an API GL-4 (SAE 75W/90) gear lubricant.

Always consult your vehicle owner’s manual for the manufacturer’s lubricant recommendations.